

This is a dry granular product that increases the total hardness in pool water to the recommended range.

DIRECTIONS FOR USE

Test for calcium hardness with a reliable test kit. The desired range for calcium hardness is as follows:

Vinyl Pools	200-300 ppm
Tile and Exposed Aggregate Pools	200-400 ppm
Marcite, Fiberglass or Painted Pools	250-400 ppm

If the calcium hardness tests less than the desired range, add this product according to the chart below. Place this product into a plastic bucket already filled with swimming pool water. Do this in a ration of up to 2 pounds of product per approximate 5-gallon bucket of water. Slowly pour this solution around the perimeter of the swimming pool while the circulating system is operating. In a 10,000 gallon pool, do not add more than 10 pounds of this product per 2 hour period.

HOW TO INCREASE CALCIUM HARDNESS IN YOUR POOL

DESIRED INCREASE IN PPM	GALLONS IN POOL		
	5,000	10,000	20,000
10 ppm	8 oz.	1 lb.	2 lbs.
20 ppm	1 lb.	2 lbs.	4 lbs.
30 ppm	1 lb. 8 oz.	3 lbs.	7 lbs.
40 ppm	2 lbs.	4 lbs.	8 lbs.
60 ppm	3 lbs.	6 lbs.	12 lbs.
80 ppm	4 lbs.	8 lbs.	16 lbs.
100 ppm	5 lbs.	10 lbs.	20 lbs.

1.6 OZ. WILL INCREASE 1 PPM PER 10K

PRECAUTIONARY STATEMENTS

WARNING: Product generates heat when combined with water. Avoid contact with eyes and prolonged contact with skin. Do not mix with other chemicals.

FIRST AID

IF IN EYES: Immediately flush eyes with large amounts of water. Seek medical help if irritation persists.

IF ON SKIN: Wash affected area with soap and water.

IF SWALLOWED: Get medical attention.

IF INHALED: Remove to fresh air.

STORAGE AND DISPOSAL:

Store closed container in a cool, dry, well-ventilated place. When container is empty, rinse thoroughly with water, wrap securely in newspaper and place in trash collection.

Distributed By:
Robelle Industries, Inc.
60 Campanelli Drive
Braintree, MA 02184
www.robelleind.com



OTHER

REV102023